

MO-6914C-BD6-307/X81028

High-speed, Cylinder-bed, 2-needle Overlock Machine (Variable Top-feed type)

This sewing machine is the
variable top-feed type
 model MO-6900C.
 (High-speed, Cylinder-bed, 2-needle Overlock Machine)



MO-6914C-BD6-307/X81028

The cylinder bed enables the machine to demonstrate highly-reliable sewing performance and finish beautiful seams.

The machine comes with the top feed dog that moves along an ideal locus. The feed dog securely catches the material and allows the multi-layer portion of a material to be fed under it with consistency. In addition it helps finish uniform seams while preventing the presser foot from jumping and smoothly feeds the material without fail.

Compact-shape of the cylinder effectively prevents the material from being fed unevenly and from twisting in various kinds of sewing of tubular materials eg., joining sleeve cuffs of which diameter is small and blind hemming long materials.



Cylinder is best-suited to runstitching and blind hemming of tubular sewing products.

With its maximum sewing speed of 7000sti/min., the machine demonstrates its capabilities when sewing long materials.

The machine achieves the highest sewing speed among cylinder-bed, variable top-feed overlock machines. It demonstrates its sewing capabilities especially when blind hemming long materials. In addition, it is not necessary to reduce the sewing speed even if the material thickness changes by a large margin at joints or the like.

The machines can be quickly adjusted at time of material changing.

A proper combination of the presser foot pressure and the top feed dog pressure is the key to achieving a secure feed of the material without damage or jumping. For the MO-6914C, the respective pressures can be independently adjusted and the adjustment value can be visually checked. This enables the operator to reproduce the combination of pressures that best suits the type of materials to be sewn and the sewing process to be carried out.

SPECIFICATIONS

Model name	MO-6914C-BD6-307/X81028
Stitch type (in the U.S.A.)	2-needle overlock (514)
Max. sewing speed	7000sti/min (longitudinal stroke of top feed dog is 6mm or less) 6000sti/min (longitudinal stroke of top feed dog is 6~8.5mm)
Stitch length	0.8~3.5mm
Stitch adjusting method	By push-button
Needle gauge	2.0mm
Overedging width	3.2mm
Bottom differential feed ratio	For gathering 1:2.3 , For stretching 1:0.8
Needle bar stroke	24.5mm
Inclination angle of the needle	20°
Needle	DCx27
Vertical stroke of top feed dog	3.5~8.5mm
Longitudinal stroke of top feed dog	1~7.5mm
Max. lift of the presser foot	6.5mm
Max. presser foot pressure	63.7N (6.5Kg)
Bottom differential feed adjusting method	By lever (with micro-adjustment)
Top differential feed adjusting method	By lever (with micro-adjustment)
Lubrication	Automatic
Lubricating oil	JUKI Machine Oil 18 (equivalent to ISO VG18)
Micro-lifter	Provided as standard

*"sti/min" stands for "Stitches per Minute."



JUKI ITALIA S.p.A.
 20020 Lainate MI - Via Bergamo, 4
 Tel. 02937579.1 - Fax uffici 0293570164
 Fax ricambi 0293571066
<http://www.juki.it> - E-mail: info@juki.it

* Specifications and appearance are subject to change without prior notice for improvement. * Read the instruction manual before putting the machine into service to ensure safety.
 * This catalogue prints with environment-friendly soyink on recycle paper.